



550 Industrial Drive Galt,  
CA 95632  
(209) 745-2387; (209)  
745-5894 fax  
Website:

## **Carson's Coatings Multi-Bond**

### **DESCRIPTION:**

Liquid formulated product designed to enhance bonding. Carson's Multi-Bond can be used with masonry, block, brick, clay tiles, and Portland cement products. The product is tinted to assure proper coverage, and will re-emulsify one time.

### **STANDARDS:**

Carson's Multi-Bond meets ASTM C-1059-97 and C-631-81 Specifications

### **COLOR:**

Carson's Multi-Bond has a light green color that assures proper coverage of surfaces.

### **PACKAGING:**

Carson's Multi-Bond comes in a convenient (1) one gallon or a (5) five gallon bucket.

### **STORAGE:**

Carson's Multi-Bond should be stored in a cool, dry place out of the direct sunlight and other possible damage. Keep Carson's Multi-Bond above 40°F and below 110°F.

### **COVERAGE:**

The coverage of Carson's Multi-Bond will vary due to job conditions, method of application, weather conditions, and whether Carson's Multi-Bond has been diluted. As a rule of thumb, (1) one gallon of Carson's Multi-Bond will cover approximately 200-300 square feet per pail.

### **AREA OF USE:**

1. One Coat products
2. Brown Coat
3. Stucco
4. Masonry
5. Poured-in-place and/or Tilt-up concrete
6. Painted surfaces
7. Approved Carson's Coatings Base Coats

### **SURFACE PREPARATION:**

Make sure that all surfaces to be covered are free of all dirt, oil, efflorescence and foreign matter.

### **MIXING:**

Shake or mix the Multi-Bond thoroughly, immediately prior to use.

### **APPLICATION:**

Carson's Multi-Bond can be used with masonry, block, brick, clay tile, Portland cement products, etc. Apply to wall with a brush, a roller, or a sprayer. This product can be painted on in a single

application, one to five days prior to application of cementitious materials, providing it does not get wet. This product will re-emulsify one time.

### **PATCHING:**

Carson's Multi-Bond may be used as patching cement. Mix one part Carson's Multi-Bond to one part water, three parts sand, and two parts cement. Mix into a paste. Depending on climactic conditions and temperature, pot life of material should be two to six hours.

### **CLEANUP:**

Cleanup can be done with water and rag or brush immediately after use.

**DO NOT** allow to dry before cleanup.

### **LIMITATIONS:**

**DO NOT** apply Carson's Multi-Bond when the temperature is below 40°F or above 100°F. This range of temperature must be kept for 48 hours to ensure proper curing!

**DO NOT** saturate surface with water prior to applying Carson's Multi-Bond.

**DO NOT** apply Carson's Multi-Bond until surface is free of all contaminants.

### **SAFETY:**

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

### **KEEP OUT OF REACH OF CHILDREN**

### **DISCLAIMER:**

Carson's Coatings [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN.

The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed

defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use of the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

### **CLAIMS:**

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Carson's Coatings reasonable charges, including travel and labor associated with investigation of such claim.

### **TECHNICAL ASSISTANCE:**

Technical assistance and information is available by calling Carson's Coatings at (209) 745-2387 or FAX (209) 745-5894 or by e-mail at "info@carsoncoatings.com".

### **WARRANTY:**

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.